

Datasheet 1/3

AIS23

AIS Stainless Steel Antenna 0.95m, 3dB

- Light weight stainless steel antenna ideal for power and sailing hoats
- Including mast mount
- Easy to install
- Full 1/2 λ antenna (156-162.5 MHz)
- Full omni-directional radiation pattern
- No groundplane needed

Electrical Specifications:		
Frequency	156 - 162.5 MHz (Int. Maritime VHF-band)	
Impedance	50 ohm	
Polarisation	Vertical	
Gain	3 dB (Marine), 0 dBd, 2.1 dBi	
Bandwidth	6.5 MHz	
VSWR	< 1.5	
Max. Power	50 W	

Mechanical Specifications:				
Color	Polished stainless steel			
Height	Approx. 950 mm			
Weight	120 g			
Mounting	On bracket (or pole with optionally Mounting Kit)		0	
Materials	Stainless steel, POM and chrome plated brass			
Operating temperature	-40C to +70C			
Connector 1	UHF-female			
Cable	No cable supplied			
Mounting place	On mast etc.			
Ingress Protection	IP66			
Serial no.	On product label			







Datasheet 2/3

Ordering information:

Part no. 12023-211 (Wall Mount Kit 1000-210 included), (in polybag)



Radiation Pattern 0° -30° 30° 10dB -60 60° 0, -10 -90 90° 1̃20° -120 -150 150∘ $\pm 180^{\circ}$





Datasheet 3 / 3



