



## 22" DATA SHEET FOR 100% DIMMABLE MARINE MONITOR IN VARIUS OPTIONS

### *Diagonal Size 22"*

Order Code, see note.	MAL22G1
SPECIFICATIONS	
Backlight Brightness:	300 cd/m <sup>2</sup>
Contrast:	800:1
Format:	16:9
Backlight Type:	LED
Dimming Range:	0 – 100%
Resolution Native:	1920 x 1080
Scaling:	1:1, 4:3, 5:4, 16:9, 16:10
Active Display Area:	476 x 268 mm
Resolution Range:	
VGA 640 x 480	✓
SVGA 800 x 600	✓
XGA 1024 x 768	✓
SXGA 1280 x 1024	✓
HD 1080 x 1080	✓



Monitor shown with dimmer

Voltage, temp., connections	
Input Voltage DC & AC. Adapter incl.	12V±10% or 100 – 240 VAC
Operating Temp.:	5° to 40° C
Mounting:	Front Frame XAVLD98422 VESA 100mm x 100mm
Dimensions without frame in mm	W 537 x H 328,8 x D 59
Speaker 2 x 3.5mm jack plug	✓
USB Hub:	N. A
Warranty:	2 years
Variations and Input	
Signal Input:	
• Audio	✓
• VGA	✓
• DVI-I	✓
• S-Video	✓
• BNC Composite video source	✓
Dimming/OSD external, RJ45	✓
Power Ext. Adapter W (Stand by):	40 W (2 W)

COMMON SPECIFICATIONS ACCESSORIES	
	Order code
Dimmer f. 1 monitor flush mount	XAVL98501
Dimmer f. 2 monitors flush mount	XAVL98502
Dimmer f. 4 monitors flush mount	XAVL98504
Classic-Foot option:	XAVL98201
Slim-Foot option:	XAVL98200
Frame for build in (MAL22XX)	XAVL98422
<b>Note:</b> Protective glass will be available later Monitor can be ordered with Touch control MAL21G1T	
For additional information's plc. check our web page: <a href="http://www.caspelektronik.com">www.caspelektronik.com</a>	

Dealer Details: