



15" DATA SHEET FOR 100% DIMMABLE MARINE MONITOR IN VARIUS OPTIONS

Diagonal Size 15"

Order Code, see note.	MAL15G1
SPECIFICATIONS	
Backlight Brightness:	350 cd/m ²
Contrast:	800:1
Format:	4:3
Backlight Type:	LED
Dimming Range:	0 – 100%
Resolution Native:	1024 x 768
Scaling:	1:1, 4:3, 5:4, 16:9, 16:10
Active Display Area:	304 x 228 mm
Resolution Range:	
VGA 640 x 480	✓
SVGA 800 x 600	✓
XGA 1024 x 768	✓
SXGA 1280 x 1024	N.A.



Monitor shown with frame and dimmer

Voltage, temp., connections	
Input Voltage DC & AC. Adapter incl.	12V _{+10%} or 100 – 240 VAC
Operating Temp.:	5° to 40° C
Mounting:	Front Frame XAVLD98415 VESA 75mm x 75mm and 100mm x 100mm
Dimensions without frame in mm	W 347,4 x H 271,4 x D 58
Speaker 2 x 3.5mm jack plug	✓
USB Hub:	N. A
Warranty:	2 years

Variations and Input	
Signal Input:	
• Audio	✓
• VGA	✓
• DVI-I	✓
• S-Video	✓
• BNC Composite video source	✓
Dimming/OSD external, RJ45	✓
Power Ext. Adapter W (Stand by):	20 W (2.5W)

COMMON SPECIFICATIONS ACCESSORIES	
	Order code
Dimmer f. 1 monitor flush mount	XAVL98501
Dimmer f. 2 monitors flush mount	XAVL98502
Dimmer f. 4 monitors flush mount	XAVL98504
Classic-Foot option:	XAVL98201
Slim-Foot option:	XAVL98200
Frame for build in (MAL15XX)	XAVL98415

Note:
Monitor can be ordered with front IP 65 Glass MAL15G1G
Monitor can be ordered with Touch control MAL15G1T

For additional information's plc. check our web page:
www.caspelektronik.com

Dealer Details: