



19" DATA SHEET FOR 100% DIMMABLE MARINE MONITOR IN VARIUS OPTIONS

Diagonal Size 19"

Order Code, see note.	MAL19G1
SPECIFICATIONS	
Backlight Brightness:	300 cd/m ²
Contrast:	1000:1
Format:	5:4
Backlight Type:	LED
Dimming Range:	0 – 100%
Resolution Native:	1280 x 1024
Scaling:	1:1, 4:3, 5:4, 16:9, 16:10
Active Display Area:	376 x 301 mm
Resolution Range:	
VGA 640 x 480	✓
SVGA 800 x 600	✓
XGA 1024 x 768	✓
SXGA 1280 x 1024	✓



Monitor shown with frame and dimmer

Voltage, temp., connections	
Input Voltage DC & AC. Adapter incl.	12V±10% or 100 – 240 VAC
Operating Temp.:	5° to 40° C
Mounting:	Front Frame XAVLD98419 VESA 100mm x 100mm
Dimensions without frame in mm	W 429,2 x H 354,2 x D 65
Speaker 2 x 3.5mm jack plug	✓
USB Hub:	N. A
Warranty:	2 years
Variations and Input	
Signal Input:	
• Audio	✓
• VGA	✓
• DVI-I	✓
• S-Video	✓
• BNC Composite video source	✓
Dimming/OSD external, RJ45	✓
Power Ext. Adapter W (Stand by):	30 W (4,5W)

COMMON SPECIFICATIONS ACCESSORIES	
	Order code
Dimmer f. 1 monitor flush mount	XAVL98501
Dimmer f. 2 monitors flush mount	XAVL98502
Dimmer f. 4 monitors flush mount	XAVL98504
Classic-Foot option:	XAVL98201
Slim-Foot option:	XAVL98200
Frame for build in (MAL19XX)	XAVL98419OSD
Note:	
Protective glass will be available later Monitor can be ordered with Touch control MAL19G1T	
For additional information's plc. check our web page: www.caspelektronik.com	

Dealer Details: